

Product Data Sheet

6. Non return valves

6.02 Swing check valve

Swing check valve metal seated (TKH) PN10/16

Material EN 1563 EN-GJS-400-15

Design Std. EN 12334

Coating Epoxy GSK RAL-GZ 662

Approval



RAL GÜTEZEICHEN

kiwa

Kolk swing check valves are made of ductile iron GJS-400/500 (DIN1693 GGG-40/50). Face to face acc. to DIN-EN 558/48-F6, flange drilling acc. to EN 1092-2 (ISO 7005-2). Epoxy coated (Resicoat®) acc. to EN 14901 (DIN 30677-2) and GSK certified (RAL-GZ 662).



Swing check valve metal seated (TKH) PN10/16

Article	Article Nr.	PN	ø DN [mm]	L [mm]	L1 [mm]	H [mm]	Holes # [DN]	ø K [mm]	ø S [mm]	G [kg]					
TKH 50	6.02TKH1.000020	PN10/16	50	200	117	162	4	125	19	11					
TKH 65	6.02TKH1.000030	PN10/16	65	240	122	178	4	145	19	14					
TKH 80	6.02TKH1.000040	PN10/16	80	260	146	208	8	160	19	18					
TKH 100	6.02TKH1.010010	PN10/16	100	300	165	241	8	180	19	29					
TKH 125	6.02TKH1.010020	PN10/16	125	350	184	300	8	210	19	36					
TKH 150	6.02TKH1.010030	PN10/16	150	400	202	328	8	240	23	47					
TKH 200	6.02TKH2.020010	PN10	200	500	274	489	8	295	23	97					
TKH 250	6.02TKH2.020020	PN10	250	600	314	565	12	350	23	147					
TKH 300	6.02TKH2.030010	PN10	300	700	375	656	12	400	23	204					